

DIGITAL AUDIO

POWERSHAPE 2.1COMPACT AMPLIFIER

ÖVERVIEV

20W per channel stereo + 25W subwoofer amplifier

RS-232, Ethernet and USB Control

Power save feature

IR remote option

Onboard EQ, Dynamics, Crossover, Gain Control

The PowerShape 2.1 offers a reliable, cost effective solution for small and midsize installations. This tamper resistant audio solution is intuitive and easily configurable giving you all the power and flexibility you need.



Analog and digital inputs

feed a proprietary digital signal processing engine before amplification. A high performance Class-D amplifier provides 20W per channel of stereo amplification with an additional 25W sub woofer channel.

Customize the audio output to fit any installation with the onboard audio shaping suite that includes 5 band EQ, compression, stereo widening, gain control, and crossover. The PowerShape 2.1 is easily configurable via USB with a downloadable PC application or over Ethernet or RS-232.

With quality audio and a robust feature set, the compact PowerShape 2.1 is ideal for many small to midsized installations including residential, corporate, government, and educational facilities.

| Parameter | Specification | Notes |
|-------------------------|----------------------------|---------------------------------|
| Speaker Outputs | | |
| Frequency Response | 20Hz to 20kHz | +0, -3dB |
| Dynamic Range | >90 dB | A-weighted, typical |
| HF Output Power (2) | 20 Watts | 4-8 Ω Stereo |
| Sub Output Power (1) | 25 Watts | 4-8 Ω Mono |
| HF THD+N | 0.16%* | 20 watts into 8Ω, 20-20kHz |
| Sub THD+N | 0.02%* | 25 watts into 8Ω, 20-20kHz |
| Analog Input (Stereo) | -10dBV | 10 kΩ Input Impedance |
| Digital Inputs (Stereo) | | Stereo S/PDIF Coax or Optical |
| Infrared (IR) | 38kHz | Front Panel IR Receiver |
| Compressors | User Adjustable | Digital Signal Processing (DSP) |
| Equalizers | | |
| Crossovers | | |
| System Control | Ethernet, RS-232, USB | |
| External Power Supply | 24VDC, 60W | |
| Box Dimensions | 5.45" W x 1.75" H x 6.8" D | |
| Weight | 1.25 lb. (0.57 kg) | |

FOR ORDERS CONTACT:

sales@digitalaudio.com 952-401-7700 @ 2013 DIGITAL AUDIO LARS


© 2013 DIGITAL AUDIO LABS. Subject to change without notice.

DIGITAL AUDIO LABS


1266 PARK RD CHANHASSEN, MN 55317 WWW.DIGITALAUDIO.COM SALES@DIGITALAUDIO.COM (952) 401 - 7700



DIGITAL AUDIO



Conference Room/Classroom #2



FOR ORDERS CONTACT:

sales@digitalaudio.com 952-401-7700

© 2013 DIGITAL AUDIO LABS. Subject to change without notice.

DIGITAL AUDIO LABS

1266 PARK RD CHANHASSEN, MN 55317 WWW.DIGITALAUDIO.COM SALES@DIGITALAUDIO.COM (952) 401 - 7700